

Slide Room Track / Leak Plug Installation

- 1) Pre-trim track plug; measure the entire visible track & add an additional 1" to go past the bulb / wiper seal (towards the RV). This also allows a little play room, which can be trimmed off at the T molding end once in place. The goal is to fill the entire visible portion of the track as much as possible.
- 2) Start inserting in the track towards the bulb / wiper seal first. You want to push it in past the rubber so it fills the entire track. You may need to trim off a tab section so its even with the sections without the tabs, in order to get past the bulb /wiper seal area. Push the trimmed plug in place. It may be nice to use a flat head screw driver or other item to assist in pushing this starting section in place, as it will be a little bit more challenging with just your fingers.
- 3) Continue installing track plug all the way down to the opposite end. Push the Track Plug straight back into the track with minimal stretching until it stops. The sections without the tabs will stick out just a little bit (about 1/8"), when pushed back in properly. Use these sections to push back in place. The tabs will be fully sticking out. The tabs allow you to grab and move the plug around to assist while putting in place & when removing.
- 4) Its best to do the final trim at the end once most all is put in place. Hold the plug up to the end, mark and then cut/ trim. Push the remaining section in place.
- 5) Note: material will stretch slightly both ways to help fill in track. Its best not to stretch it much, but a little bit is fine. You can also smooch the plug material together (making it shorter) to help if the plug is slightly to long. Use the tabs to pull in the direction you want it to go.
- 6) Remove, by pulling on the tabs, roll up and store in a clear bag when not using. Remember to remove before bringing your slides in. Place one of the supplied logo stickers next to your power slide button as a reminder.

